

12X12X6 PREMIUM SERIES



Mounting Feet



Mounting Flanges



Features & Benefits

- **Quality material** – bases, opaque covers and clear covers are all made of high-impact, UV resistant polycarbonate.
- **Flexible interior mounting** – features the unique and patented Integra adjustable depth “T-Rail” back panel mounting system (back panel and adjustable brackets sold separately).
- **Wide range** of sizes, configurations and accessories provides capabilities for every application.
- **Brass inserts** – in corner bosses for easy component installation.
- **Standard color** – light gray with a gloss finish.
- **UL-50 / c-UL Listed** (files # E229365, # E207562)

Mechanical & Thermal	Test Spec.	Unit	Rating
Instrumented Dart Impact @ 73° F	-	in-lbs	565
Falling Ball Impact @ 73° F	UL-746	in-lbs	900
Deflection Temperature @ 264 psi	ASTM D648	Deg. F	270
Modulus of Elasticity	ASTM D790	ksi	340
Temperature Range	-	Deg. F	-40 to 265
Flame Rating - UL	UL 94	-	5VA
Outdoor UV Exposure	UL	-	f1

Part Number	4X IP66	6P IP68	Hinged Cover	Screw Cover	Opaque Cover	Clear Cover	Mounting Feet	Mounting Flange	Stainless Steel Locking Latch	Non-Metallic Locking Latch
H121206S	✓	✓		✓	✓		✓			
H121206SC	✓	✓		✓		✓	✓			
H121206SF	✓	✓		✓	✓			✓		
H121206SCF	✓	✓		✓		✓		✓		
H121206H	✓		✓	✓	✓		✓			
H121206HC	✓		✓	✓		✓	✓			
H121206HF	✓		✓	✓	✓			✓		
H121206HCF	✓		✓	✓		✓		✓		
★ H121206HLL	✓		✓		✓		✓		✓	
★ H121206HCLL	✓		✓			✓	✓		✓	
H121206HFLL	✓		✓		✓			✓	✓	
H121206HCFLL	✓		✓			✓		✓	✓	
H121206HNL	✓		✓		✓		✓			✓
H121206HCNL	✓		✓			✓	✓			✓
H121206HFNL	✓		✓		✓			✓		✓
H121206HCFNL	✓		✓			✓		✓		✓
H121206H-6P	✓	✓	✓	✓	✓		✓			
H121206HC-6P	✓	✓	✓	✓		✓	✓			
H121206HF-6P	✓	✓	✓	✓	✓			✓		
H121206HCF-6P	✓	✓	✓	✓		✓		✓		

★ **POPULAR CONFIGURATIONS:** Most popular configurations are available for *QuickShip*. Please send requests to customerservice@integraenclosures.com to take advantage of our *QuickShip* option.

